



4.8kW WATER COOLED SPLIT SYSTEM



CODE: 1POR-2006

ACCESSORIES



DISTRIBUTION BOARDS



SINGLE PHASE
EXTENSION LEADS



SINGLE LANE
CABLE CROSSOVER



Designed for a fast installation and start up, the unit is useful where access to the outside is difficult and some distance from internal rooms as the outdoor unit (heat exchange) can be placed up to 30 meters. Economical, the unit does not require continuous water. Quiet in operation enables them to be used on general offices as well. With durable metal construction and 4 wheeled, they are space-efficient as they don't need to have a hot air exhaust duct. A control panel provides ease of use and contains self-diagnostic function. Choice of continuous operation or automatic timer is also available.

PRODUCT SPECIFICATIONS

POWER REQUIREMENTS

Power Supply	50Hz / Single / 220V / 240V
--------------	-----------------------------

AREA OF USE

Industrial
Commercial
Emergency
Events
Computer Server Rooms

TECHNICAL INFORMATION

Total cooling capacity (kW)	4.8kW
Operating Range (°C)	18 - 45
Current consumption (Amps)	10

Power consumption (kW)	2.2
Noise level (at 3m)	56 / 52
Hose length (standard) (m)	10
Hose length (max.) (m)	30
Refrigerant	R410A

PHYSICAL INFORMATION	INDOOR	OUTDOOR
Height (mm)	865	505
Width (mm)	705	200
Length (mm)	350	500
Weight (kg)	91	22

FEATURES

Water-Cooled
Two Speed fan
No need for exhaust duct
Off-timer
Condensate pump included
One touch connector

SAFETY DEVICES

Compressor time delay
Compressor overload protection
High pressure switch
Thermostat
Self-diagnostic functions

F 1300 487 247
E info@aircon.com.au

www.aircon.com.au

1800 626 996

Cooling Chillers Reverse Cycle Heating Refrigeration Dehumidification Ventilation Power

SYDNEY | MELBOURNE | BRISBANE | PERTH | ADELAIDE | HOBART | CANBERRA