



4.8kW WATER COOLED SPLIT SYSTEM



CODE: 1POR-2006

ACCESSORIES



DISTRIBUTION BOARDS



SINGLE PHASE EXTENSION LEADS



SINGLE LANE CABLE CROSSOVER



Designed for a fast installation and start up, the unit is useful where access to the outside is difficult and some distance from internal rooms as the outdoor unit (heat exchange) can be placed up to 30 meters. Economical, the unit does not require continuous water. Quiet in operation enables them to be used on general offices as well. With durable metal construction and 4 wheeled, they are space-efficient as they don't need to have a hot air exhaust duct. A control panel provides ease of use and contains self-diagnostic function. Choice of continuous operation or automatic timer is also available.

PRODUCT SPECIFICATIONS

POWER REQUIREMENTS

Power Supply 50Hz / Single / 220V / 240V

AREA OF USE

Industrial

Commercial

Emergency

Events

Computer Server Rooms

TECHNICAL INFORMATION

Total cooling capacity (kW) 4.8kW

Operating Range (°C) 18 - 45

Current consumption (Amps) 10

Power consumption (kW) 2.2

Noise level (at 3m) 56 / 52

Hose length (standard) (m) 10

Hose length (max.) (m) 30

Refrigerant R410A

PHYSICAL INFORMATION

Height (mm) 865 505

Width (mm) 705 200

Length (mm) 350 500

Weight (kg) 91 22

FEATURES

Water-Cooled

Two Speed fan

No need for exhaust duct

Off-timer

Condensate pump included

One touch connector

SAFETY DEVICES

Compressor time delay

Compressor overload protection

High pressure switch

Thermostat

Self-diagnostic functions

F 1300 487 247

E info@aircon.com.au

www.aircon.com.au

1800 626 996

❄️ Cooling ❄️ Chillers 🔁 Reverse Cycle 🔥 Heating 📄 Refrigeration 💧 Dehumidification 🌀 Ventilation ⚡ Power

SYDNEY | MELBOURNE | BRISBANE | PERTH | ADELAIDE | HOBART | CANBERRA