



# 250kW AIR COOLED CHILLER



CODE: 1 CHL-0250



## ACCESSORIES



CHILLED WATER PIPE WORK



CHILLED WATER PUMPS



CHILLED WATER STRAINER

The 250kW Chiller is Air cooled and has two semi-hermetic compressor that provides numerous stages of capacity control. All units are skid mounted with interlocking variable speed/variable volume centrifugal pumps to match the system requirements. Units require one 240amp hard wired or power lock connect.

## PRODUCT SPECIFICATIONS

### POWER REQUIREMENTS

- 3 P 2 x 120 Amp Hard Wire
- 110 Required Curcuit Breaker (amps)

### EQUIPMENT TYPE

- Reverse Cycle Unit

### AREA OF USE

- Industrial
- Commercial
- Manufacturing
- Emergency

### TECHNICAL INFORMATION

|                             |              |
|-----------------------------|--------------|
| Total Cooling Capacity (kW) | 250          |
| Heating Capacity (kW)       | 260          |
| Water Flow Rate (l/s)       | 12           |
| Stages                      | 4            |
| Refrigerant                 | R22 or R407C |

### FEATURES

- Remote Control
- Three Phase Power Required
- Plug and Play Device
- Comes in both hardwired or pluggabled device
- Quick connect pipework

### PHYSICAL INFORMATION

|             |      |
|-------------|------|
| Height (mm) | 2050 |
| Width (mm)  | 2300 |
| Length (mm) | 2050 |
| Weight (kg) | 3200 |

F 1300 487 247  
E info@aircon.com.au

www.aircon.com.au

1800 626 996