



# WSC-F-6650



## 6.6KW SPLIT PORTABLE AIR CONDITIONER



### ACCESSORIES



DISTRIBUTION BOARDS



SINGLE PHASE  
EXTENSION LEADS



SINGLE LANE  
CABLE CROSSOVER

The WSC-6650 water cooled split air conditioner is a low noise functioning unit. It has a functioning indoor unit range of 10-30C whilst the outdoor range is 10-40C. A great unit that circulates air flow at 45/90 angles. It has a 30m maximum distance between internal and external units, a 3 speed motor fan, electric and water flexible pipe with rapid connection.

## PRODUCT SPECIFICATIONS

POWER REQUIREMENTS		TECHNICAL INFORMATION				PHYSICAL INFORMATION		INDOOR	OUTDOOR
Power Supply	50Hz / Single / 230V	Cooling capacity* (kW)	6.6			Height (mm)	1030	460	
15 Amp - Outlet Required		Current consumption* (Amps)	12			Width (mm)	815	582	
EQUIPMENT TYPE		Power consumption* (kW)	2.7			Length (mm)	360	360	
Water Cooled (Split)		Indoor Noise Level at 3m (dB)	49			Weight (kg)	105	22	
Portable Unit		Max. distance between two units (m)			30				
AREA OF USE		Indoor Unit Airflow	MAX	NORMAL	LOW				
Industrial		Fan Speed (l/s)	416	388	319				
Commercial		Outdoor Unit Airflow (l/s)			583				
Emergency		High Efficiency Compressor			Rotary				
Events		Refrigerant			R407C				
		* 26°C 55% indoor, 30°C Outdoor							

\* Product models may vary from picture shown

F 1300 487 247  
E info@aircon.com.au

www.aircon.com.au

1800 626 996

Cooling Chillers Reverse Cycle Heating Refrigeration Dehumidification Ventilation Power

SYDNEY | MELBOURNE | BRISBANE | PERTH | ADELAIDE | HOBART | CANBERRA